

(12) PATENT APPLICATION PUBLICATION

(21) Application No.202011033365 A

(19) INDIA

(22) Date of filing of Application :04/08/2020

(43) Publication Date : 11/02/2022

(54) Title of the invention : DEVICE FOR INDICATING LOW LEVEL OF A LIQUID IN A BATTERY ASSEMBLY

(51) International classification	:H01M0002100000, B60K0001040000, H04B0001388800, H01M0002020000, H01M0010625000	(71) Name of Applicant : 1)Chitkara Innovation Incubator Foundation Address of Applicant :SCO: 160-161, Sector - 9c, Madhya Marg, Chandigarh- 160009, India. Chandigarh India
(31) Priority Document No	:NA	(72) Name of Inventor :
(32) Priority Date	:NA	1)RAMNEET
(33) Name of priority country	:NA	2)GUPTA, Deepali
(86) International Application No	:NA	3)MUDITA
Filing Date	:NA	4)GUPTA, Sheifali
(87) International Publication No	: NA	5)AHUJA, Sachin
(61) Patent of Addition to Application	:NA	6)MADHUKAR, Mani
Number	:NA	7)GUPTA, Raman
Filing Date	:NA	8)AILAWALIA, Praveen
(62) Divisional to Application Number	:NA	9)GUPTA, Rupesh
Filing Date	:NA	10)GUPTA, Kamali

(57) Abstract :

The present disclosure relates to a battery assembly (100) configured to indicate low level of a liquid in the battery assembly, said battery assembly comprising: a lid (102) provided at the top portion of the battery case and adapted to cover the hole; a cable (104) coupled to the lid such that when the lid covers the hole, a predefined length of the cable is inserted into the hollow space; and an alarm circuit (200) comprising an alarm (204) and a power source (208) to supply power to the alarm, wherein, when the liquid in the hollow space reduces to a point where it is not in contact with at least a portion of the cable, power from the power source is supplied to the alarm to enable to alarm to activate and indicate a requirement for adding liquid to the hollow space of the battery assembly.

No. of Pages : 16 No. of Claims : 7