(19) INDIA

(51) International

(86) International

(87) International

Publication No

Filing Date

Filing Date

Application Number

Filing Date

(62) Divisional to

(61) Patent of Addition :NA to Application Number

Application No

classification

(22) Date of filing of Application :06/09/2022

(43) Publication Date: 20/01/2023

(54) Title of the invention: AUTOMATED CUP DISPENSER ASSEMBLY

:A61P0025240000, C07J0041000000,

A61P0025260000, C05G0003600000,

A61P0003040000

:NA

:NA

: NA

:NA

:NA

:NA

(71)Name of Applicant:

1)Chitkara University

Address of Applicant: Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala ------

2) Chitkara Innovation Incubator Foundation

Name of Applicant: NA Address of Applicant: NA (72)Name of Inventor:

1)GUPTA, Rupesh

Address of Applicant :Department of Mechatronics Engineering, Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala ------

2)SINGLA, Jatin

Address of Applicant :Department of Mechatronics Engineering, Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala ------

3)ARYA, Tanmay

Address of Applicant :Department of Mechatronics Engineering, Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala ------

4)MALIK, Nitish

Address of Applicant :Department of Mechatronics Engineering, Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala ------

5)GUPTA, Sheifali

(57) Abstract:

Disclosed are embodiments of a cup dispenser assembly 100 that accommodate a stack of cups and dispense the cup, automatically. The assembly 100 includes a body 104 configured to receive the stack of cups, and a releasing device 112 attached to the body that upon actuation of an actuator 114, dispenses a single cup from bottom of the stack of the cup. Additionally, a receiving member 116 is configured to receive the dispensed cup from the body, where the receiving member 116 is configured such that it moves towards a user upon receiving the dispensed cup. The process of using the cup dispenser assembly involves pushing the actuator 114 and the cup positioned at bottom of the stack of cups is dispensed easily.

No. of Pages: 19 No. of Claims: 7