

(12) PATENT APPLICATION PUBLICATION

(21) Application No.202211055067 A

(19) INDIA

(22) Date of filing of Application :26/09/2022

(43) Publication Date : 13/01/2023

(54) Title of the invention : AN APPARATUS TO SECURE A MULTILAYER CAKE AND A METHOD TO OPERATE THE SAME

(51) International classification :C12M0001120000, A21B0003130000, C12M0001240000, B60R0011000000, B62B0003020000

(86) International Application No :NA
Filing Date :NA

(87) International Publication No : NA

(61) Patent of Addition to Application Number :NA
Filing Date :NA

(62) Divisional to Application Number :NA
Filing Date :NA

(71)Name of Applicant :

1)Chitkara University

Address of Applicant :Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala -----

2)Chitkara Innovation Incubator Foundation

Name of Applicant : NA

Address of Applicant : NA

(72)Name of Inventor :

1)SINGH, Gurpreet

Address of Applicant :Assistant Professor, Department of Mechatronics Engineering, Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala -----

2)VOHRA, Amit

Address of Applicant :Department of Culinary Arts, CCHM, Escoffier Block, Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala -----

(57) Abstract :

The present disclosure relates to an apparatus to secure a multilayer cake and a method to operate the same. The apparatus includes a base shelf configured to secure a bottom layer of the multilayer cake. The apparatus also includes at least one shelves. Each of the at least one shelves and the base shelf are mounted parallel to each other. The apparatus also includes a cylindrical tube placed at a centre position of each of the at least one shelves, wherein each of the at least one shelves are configured to support cakes of different sizes. The apparatus also includes a platform housed inside the cylindrical tube. The platform is configured to be operated along an internal surface of the cylindrical tube. The platform is operated via a motor, wherein the motor is operatively coupled to a pair of brackets.

No. of Pages : 15 No. of Claims : 7