

(54) Title of the invention : MEASURING TAPE WITH INTEGRATED SCRIBER TOOL

(51) International classification :G01B0003108400, G01B0003108900, A61M0005168000, F21Y0115100000, H04M0001020000

(86) International Application No :NA  
Filing Date :NA

(87) International Publication No : NA

(61) Patent of Addition to Application Number :NA  
Filing Date :NA

(62) Divisional to Application Number :NA  
Filing Date :NA

(71)Name of Applicant :  
**1)Chitkara University**  
 Address of Applicant :Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala -----

**2)Chitkara Innovation Incubator Foundation**  
**Name of Applicant : NA**  
**Address of Applicant : NA**

(72)Name of Inventor :  
**1)KUMAR, Naveen**  
 Address of Applicant :Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala -----

**2)KAUSHAL, Rajesh Kumar**  
 Address of Applicant :Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala -----

**3)KUMAR, Mohit**  
 Address of Applicant :Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala -----

**4)SINGHAL, Shilipi**  
 Address of Applicant :Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala -----

**5)MANSI**  
 Address of Applicant :Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala -----

(57) Abstract :

A measuring tape 100 is disclosed, the measurement tap 100 having a housing 102 where a roll of tape 104 disposed in an interior volume of the housing 102. One end of the roll is attached inside the interior volume, and a hook 106 is attached on another end of the roll, where the hook 106 enables a user to pull the tape from the housing. Additionally, a locking mechanism 108 attached to the housing to lock the retracted tape at a fixed distance. A protractor 110 attached to the housing to measure angles easily. Furthermore, a scribe tool 112 detachably coupled to the housing to enable a user to cut a workpiece, the user exerts pressure on the scribe tool and moves the housing in such a manner that facilitates cutting of a required area of the workpiece.

No. of Pages : 17 No. of Claims : 7