(12) PATENT APPLICATION PUBLICATION

(21) Application No.202311054603 A

(19) INDIA

(22) Date of filing of Application :14/08/2023

(43) Publication Date : 08/09/2023

(54) Title of the invention : A SYSTEM AND METHOD FOR ENHANCING SECURITY OF RIDESHARING IN CAB SERVICE

(51) International classification	:G06Q0050300000, G01C0021340000, H04W0004400000, A61B0034200000, G01C0021360000
(86) International Application No Filing Date	:NA :NA
(87) International Publication No	: NA
(61) Patent of Addition to Application Number Filing Date	:NA :NA
(62) Divisional to Application Number Filing Date	:NA :NA

(71)**Name of Applicant :**
  1)**Chitkara University**
    Address of Applicant :Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala ----------- -----------
  2)**Bluest Mettle Solutions Private Limited**
Name of Applicant : NA
Address of Applicant : NA
(72)**Name of Inventor :**
  1)**MISHRA, Rahul**
Address of Applicant :ODC-4, Panchshil Tech Park, inside Courtyard by Marriott premises, Hinjewadi Phase - 1, Pune - 411057, Maharashtra, India. Pune ----------- -----------
  2)**PANDEY, Sakshi**
Address of Applicant :ODC-4, Panchshil Tech Park, inside Courtyard by Marriott premises, Hinjewadi Phase - 1, Pune - 411057, Maharashtra, India. Pune ----------- -----------
  3)**MANTRI, Archana**
Address of Applicant :Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala ----------- -----------

(57) Abstract :
Embodiments of the present disclosure relates to a system (100) and method (300) for enhancing security of ridesharing in cab service. The system comprises a processor (202) coupled to a memory (204). The memory (204) stores processor-executable instructions. The processor (202) is configured to verify a rider identity and a driver identity. Further, the processor (202) is configured to transmit a ride request from a rider user to a driver. Next, the processor (202) is configured to track a current location of the rider based on the ride request. In the end, the processor (202) is configured to trigger an alert signal based on the tracked location.

No. of Pages : 24 No. of Claims : 10