(12) PATENT APPLICATION PUBLICATION

(19) INDIA

(22) Date of filing of Application :04/09/2023

(43) Publication Date : 06/10/2023

(71)Name of Applicant : 1)Chitkara University Address of Applicant : Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, :H01M0010440000, H02J0007000000, (51) International India. Patiala -----G09G0003360000, H01L0029240000, classification 2)Bluest Mettle Solutions Private Limited H01L0029490000 Name of Applicant : NA (86) International :NA Address of Applicant : NA Application No :NA (72)Name of Inventor : Filing Date 1)MISHRA, Rahul (87) International : NA Address of Applicant :ODC-4, Panchshil Tech Park, inside Publication No Courtyard by Marriott premises, Hinjewadi Phase - 1, Pune -(61) Patent of Addition :NA 411057, Maharashtra, India. Pune -----to Application Number :NA 2)PANDEY, Sakshi Filing Date Address of Applicant :ODC-4, Panchshil Tech Park, inside (62) Divisional to Courtyard by Marriott premises, Hinjewadi Phase - 1, Pune -:NA Application Number 411057, Maharashtra, India. Pune ------:NA Filing Date 3)MANTRI, Archana Address of Applicant : Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala -----

SUBSTRATE

(54) Title of the invention : A SYSTEM AND METHOD FOR ELECTROSTATIC POLYMER SPRAY DEPOSITION ON A

(57) Abstract :

Embodiments of the present disclosure relates to a system (102) and method (200) for electrostatic polymer spray deposition on a substrate. In an aspect, the present disclosure discloses a system (102) for electrostatic polymer spray deposition on a substrate that utilizes electrostatic principles to control the charging and discharging of polymer particles during the spraying process, resulting in improved deposition control and optimized coatings of the substrate. The system (102) comprises a plurality of charging electrodes (104) configured to create an electric field for charging polymer particles. Further, the system (102) comprises a plurality of discharging electrodes (106), positioned proximally to the substrate, and configured to regulate a charging electrode voltage of the plurality of charging electrodes (104) and a discharging electrode voltage of the plurality of discharging electrodes (106).

No. of Pages : 21 No. of Claims : 10