(12) PATENT APPLICATION PUBLICATION

(22) Date of filing of Application :19/10/2023

## (54) Title of the invention : AUTOMATIC SHOE WASHER AND DRYING APPARATUS AND METHOD

(51) International	:A47L0023020000, A47L0023200000,	<ul> <li>(71)Name of Applicant :</li> <li>1)Chitkara University Address of Applicant :Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala</li> </ul>
classification	D06F0037420000, D06F0039140000, B41J0011000000	2)Chitkara Innovation Incubator Foundation Name of Applicant : NA
<ul> <li>(86) International Application No Filing Date</li> <li>(87) International Publication No</li> <li>(61) Patent of Addition to Application Number Filing Date</li> <li>(62) Divisional to Application Number</li> </ul>	:NA :NA : NA	Address of Applicant : NA (72)Name of Inventor : 1)SAKSHI Address of Applicant :Department of Computer Science and Applications, Sharda University, Plot No. 32, 34, Knowledge Park III, Greater Noida - 201310, Uttar Pradesh, India. Greater Noida  2)SINGLA, Parish Address of Applicant :Chitkara University Institute of Engineering and Technology, Chitkara University, Chandigarh-Patiala
Filing Date		National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala <b>3)LODHI, Sachin</b> Address of Applicant :H.No.63, Bheraghat, Jabalpur, Madhya Pradesh – 483053, India. Bheraghat

## (57) Abstract :

An apparatus (100) comprising a housing (102), a door (104), a washing unit (106), a drying unit (108), and a control unit (110). The housing (102) is configured to accommodate a shoe for washing and drying. The washing unit is configured to dispense a predefined amount of washing liquid and water. The drying unit (108) is configured to blow hot air onto the surface of the shoes. The control unit (110) is attached to the housing (102) and configured to detect the position of the shoes by the position sensor and transmit a set of signals to the control unit 110 to activate the washing unit (106) to dispense a pre-defined amount the washing liquid and water respectively and activate drying unit (108) to blow hot air on the washed shoe for drying the shoe within the housing (102).

No. of Pages : 20 No. of Claims : 10