(19) INDIA

(22) Date of filing of Application :29/02/2024

(43) Publication Date: 08/03/2024

(54) Title of the invention: AN ENCLOSURE FOR COVERING AND HANDLING A HYDROTHERMAL AUTOCLAVE

:A61B0001000000, A61B0017860000, (51) International A45D0040000000, A61F0002300000, classification

F16M0013020000

(86) International :NA Application No :NA Filing Date (87) International : NA

Publication No (61) Patent of Addition:NA to Application Number :NA Filing Date

(62) Divisional to :NA **Application Number** :NA Filing Date

National Highway, Village Jhansla, Raipura, Punjab - 140401. India, Patiala -----

2) Chitkara Innovation Incubator Foundation Name of Applicant: NA Address of Applicant: NA (72)Name of Inventor:

(71)Name of Applicant: 1)Chitkara University

1)TAKKAR, Rajat

Address of Applicant :Department of Applied Sciences, Chitkara University Institute of Engineering & Technology, Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala ------

Address of Applicant: Chitkara University, Chandigarh-Patiala

2)SHARMA, Vandna

Address of Applicant: Department of Applied Sciences, Chitkara University Institute of Engineering & Technology, Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala ------

3)KUMAR, Pankaj

Address of Applicant: Department of Applied Sciences, Chitkara University Institute of Engineering & Technology, Chitkara University, Chandigarh-Patiala National Highway, Village Jhansla, Rajpura, Punjab - 140401, India. Patiala ------

(57) Abstract:

An enclosure (100) for covering and handling a hydrothermal autoclave that includes an elongated cylindrical member (102) extending in a longitudinal axis and a cover plate (106) coupled to a top end (102-1) of the elongated cylindrical member (102). The elongated cylindrical member (102) comprises a plurality of threaded holes (104) disposed on surface of the elongated cylindrical member (102). The cover plate (106) is configured to close the top end (102-1) of the elongated cylindrical member (102). Each of the threaded holes (104) is configured to receive at least one of a locking means (108) to secure the enclosure (100) at a predefined position over the hydrothermal autoclave.

No. of Pages: 14 No. of Claims: 8