

(54) Title of the invention : COVER ASSEMBLY, BATTERY AND BATTERY PACK

(51) International classification	:H01M0050538000, H01M0050209000, G02F0001133570, H01M0050150000, H01M0050204000	(71)Name of Applicant : 1)HUIZHOU EVE POWER CO., LTD Address of Applicant :No.5, Xingyuan North Road, Sanhe Village, Tonghu Town, Zhongkai High-tech District, Huizhou, Guangdong 516039, China. ----- ----- 2)EVE POWER CO., LTD. Name of Applicant : NA Address of Applicant : NA
(31) Priority Document No	:202322678276.2	(72)Name of Inventor :
(32) Priority Date	:28/09/2023	1)FAN, Weicheng Address of Applicant :No.5, Xingyuan North Road, Sanhe Village, Tonghu Town, Zhongkai High-tech District, Huizhou, Guangdong 516039, China. Huizhou ----- -----
(33) Name of priority country	:-----	2)ZHAO, Fenfen Address of Applicant :No.5, Xingyuan North Road, Sanhe Village, Tonghu Town, Zhongkai High-tech District, Huizhou, Guangdong 516039, China. Huizhou ----- -----
(86) International Application No	:NA	3)ZHANG, Lei Address of Applicant :No.5, Xingyuan North Road, Sanhe Village, Tonghu Town, Zhongkai High-tech District, Huizhou, Guangdong 516039, China. Huizhou ----- -----
Filing Date	:NA	
(87) International Publication No	: NA	
(61) Patent of Addition to Application Number	:NA	
Filing Date	:NA	
(62) Divisional to Application Number	:NA	
Filing Date	:NA	

(57) Abstract :
Disclosed are a cover assembly, a battery and a battery pack. The cover assembly includes a cover body and an insulating member. The insulating member includes a connecting portion and a guide portion. The connecting portion is mounted to the cover body, the guide portion is provided in an annular shape and connected to a side of the connecting portion away from the cover body in a first direction. The guide portion is provided with a cavity and comprises a guide surface away from the cavity. The guide surface is an inclined surface. An orthographic projection of the guide surface in the first direction falls entirely within the connecting portion.

No. of Pages : 15 No. of Claims : 10